



SECTION A-A

(TYPICAL STREET PAVEMENT)

NOTES:

- * 1. REFER TO THE COSM TRANSPORTATION DESIGN MANUAL REQUIREMENTS FOR ALL MINIMUM PAVEMENT LAYER THICKNESS. ACTUAL THICKNESSES TO BE DETERMINED BASED ON COMPUTERIZED PAVEMENT DESIGN.
- 2. ALL UNPAVED AREA WITHIN THE LIMITS OF CONSTRUCTION SHALL BE SODDED OR SEEDS AS INDICATED PER CITY SPECIFICATION 601S - 609S AS APPLICABLE.
- 3. SLOPES OF STREET SECTION WILL BE PER THE CURRENT TRANSPORTATION MANUAL. TYPICAL 2% TOWARDS THE CURB AND GUTTER FROM PROPERTY LINE AND PARABOLIC FROM CROWN UNLESS ALTERNATE CROSS SECTION PROPOSED.
- ** 4. ALL WIDTH AND SPACING WILL BE PER CURRENT CITY CODE / DESIGN MANUAL.

| | | | |
|---|--|---|--|
| The City of San Marcos Engineering and Capital Improvements | CURRENT AS OF 1/1/2022 | TYPICAL STREET SECTION | |
| RECORD COPY SIGNED BY <hr style="width: 100%;"/> Laurie Moyer, P.E. | 1/1/2022 <hr style="width: 100%;"/> ADOPTED | THE ARCHITECT/ENGINEER ASSUMES RESPONSIBILITY FOR APPROPRIATE USE OF THIS STANDARD. | STANDARD NO. 1000S-10-SM 1 OF 1 |